




## Transient Voltage Suppressors for ESD Protection

### FEATURES

- Protects up to 4-Lines operating at 5V
- Transient protection for each line according to IEC61000-4-2(ESD):  $\pm 8\text{kV}$  (contact)  $\pm 15\text{kV}$  (air)
- Low leakage current




### Applications

- High Definition Multi-Media Interface;
- USB 1.1/2.0/3.0/3.1 Interfaces;
- Projection TV Monitors and Flat Panel Displays;
- Portable electronics.

### Electronics Parameter

Parameter	Symbol
Maximum Reverse Peak Pulse Current	$I_{PP}$
Clamping Voltage @ $I_{PP}$	$V_C$
Peak Reverse Working Voltage	$V_{RWM}$
Reverse Leakage Current @ $V_{RWM}$	$I_R$
Breakdown Voltage @ $I_T$	$V_{BR}$
Test Current	$I_T$
Forward Current	$I_F$
Forward Voltage @ $I_F$	$V_F$





MAXIMUM RATINGS(Ta=25°C unless otherwise noted)

Parameter	Symbol	Value	Unit
Peak Pulse Power (8/20μS)	Ppk	50	W
Peak Pulse Current	Ipp	3	A
ESD per IEC 61000-4-2(Air)	VESD	±15	KV
ESD per IEC 61000-4-2(Contact)		±8	
Operating Temperature Range	TJ	-55~+125	°C
Storage Temperature Range	Tstg	-55~+150	°C

ELECTRICAL CHARACTERISTICS(Ta=25°C unless otherwise noted)

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Reverse Stand-off Voltage	VRWM				5.0	V
Breakdown Voltage	VBR	IT=1mA	6.0			V
Reverse Leakage Current	IR	V=VRWM,Ta=25°C			0.2	µA
Clamping Voltage	VC	IPP=1A, tp=8/20µs		11	14	V
		IPP=3A, tp=8/20µs		15	20	
Junction Capacitance	Cj	VR=0V, f=1MHz <sub>(IO-GND)</sub>		0.2	0.3	pF
Junction Capacitance	Cj	VR=0V, f=1MHz <sub>(IO-IO)</sub>		0.2	0.3	pF



## Typical Characteristics

Fig.1 Pulse Waveform




Fig.2 Contact discharge current waveform per IEC61000-4-2




Fig.3 Power Derating Curve




Fig.4 Peak Pulse Power vs. Pulse Time




Fig.5 Clamping Voltage vs. Peak Pulse Current






Fig.6 Capacitance vs. Reverse voltage






## Typical Characteristics

Fig.7 Eye Diagram-USB3.0 mask at 5.0Gbps




Without Component

Fig.8 Eye Diagram-USB3.0 mask at 5.0Gbps




Without Component

Fig.9 Eye Diagram-USB3.1 mask at 10.0Gbps



Without Component

Fig.10 Eye Diagram-USB3.1 mask at 10.0Gbps




Without Component




## PACKAGE OUTLINE

Plastic surface mounted package; 2 leads

DFN2010-5L



### The recommended mounting pad size



### Marking

Type number	Marking code
ESDZULC5V0DKA5PA	4R2N

Notes:

1. This Footprint is for reference purpose only.



## Important Notice and Disclaimer

Jingdao Microelectronics reserves the right to make changes to this document and its products and specifications at any time without notice.

Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

Jingdao Microelectronics makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, not does Jingdao Microelectronics assume any liability for application assistance or customer product design.

Jingdao Microelectronics does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of Jingdao Microelectronics.

Jingdao Microelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of Jingdao Microelectronics.