FEATURES:
- Lower clamping voltage
- Green Molding Compound
  (No Halogen and Antimony)
- Glass Passivated Chip Junction
- High Surge Current Capability
- Designed for Surface Mount Application

MECHANICAL DATA
- Case: UMBT
- Terminals: Solderable per
  MIL-STD-750, Method 2026
- Approx. Weight: 60mg/0.0021oz

PINNING

PIN	DESCRIPTION
1	Input Pin（~）
2	Input Pin（~）
3	Output Anode（+）
4	Output Cathode（-）



UMBT Package

Maximum Ratings and Electrical characteristics

Ratings at 25°C ambient temperature unless otherwise specified.
Single phase half-wave 60 Hz, resistive or inductive load, for capacitive load current derate by 20 %.

Parameter	Symbols	BP43CUM10B-10	Units
Average Rectified Output Current	I_O	1.0	A
Peak Forward Surge Current 8.3 ms Single Half Sine Wave Superimposed on Rated Load	I_{FSM}	30	A
Maximum Forward Voltage at 1.0 A	V_F	1.1	V
Maximum DC Reverse Current at Rated DC Blocking Voltage (@VR=1000V) @T_A=25 °C @T_A=125 °C	I_R	5 40	μA
Typical Junction Capacitance（Note1）	C_j	7	pF
Typical Thermal Resistance（Note2）	$R_{\theta JA}$ $R_{\theta JC}$ $R_{\theta JL}$	45 15 25	°C/W
Operating and Storage Temperature Range	T_j, T_{stg}	-55 ~ +150	°C

Note: 1. Measured at 1MHz and applied reverse voltage of 4 V D.C.
2. Mounted on glass epoxy PC board with 4×1.5"×1.5"（3.81×3.81 cm）copper pad.

Maximum Ratings and Thermal Characteristics(TA = 25°C unless otherwise specified)

Parameter of TVS	Symbol	BP43CUM10B-10	Unit
Maximum allowable continuous AC voltage at 50-60Hz	V_{RMS}	26	V
Breakdown voltage	V_{BR}	40.9~45.2	V
Maximum allowable continuous DC voltage	V_{DC}	36.8	V
Maximum allowable clamping voltage	V_C	59.3	V
Maximum peak pulse current	I_{pp}	11.2	A
Operating and Storage Temperature Range	T_j, T_{stg}	-55 ~ +150	°C

NOTES:
1.The breakdown voltage was measured at 1mA
2. The clamping voltage was measured at 10/1000μs standard current
3. The peak pulse current was tested at 10/1000μs waveform

Fig.1 Average Rectified Output Current Derating Curve



Fig.2 Typical Reverse Characteristics



Fig.3 Typical Forward Characteristic



Fig.4 Typical Junction Capacitance



Fig.5 Maximum Non-Repetitive Peak Forward Surge Current



Fig.6 Peak Pulse Power Rating Curve



Fig.7 Forward Current Derating Curve



Fig.8 Pulse Waveform



PACKAGE OUTLINE

Plastic surface mounted package; 4 leads

UMBT



UMBT mechanical data

UNIT		A	C	D	E	H_E	g	d	e	∠
mm	max	1.8	0.20	3.8	4.0	5.1	0.82	2.7	0.70	7°
	min	1.6	0.12	3.4	3.6	4.6	0.51	2.3	0.51	
mil	max	71	7.9	150	157	201	32	106	28	
	min	63	4.7	134	142	181	20	91	20	

The recommended mounting pad size



Marking

Type number	Marking code
BP43CUM10B-10	BP43C10

Important Notice and Disclaimer

Jingdao Microelectronics reserves the right to make changes to this document and its products and specifications at any time without notice.
Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

Jingdao Microelectronics makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, not does Jingdao Microelectronics assume any liability for application assistance or customer product design.

Jingdao Microelectronics does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of Jingdao Microelectronics.

Jingdao Microelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of Jingdao Microelectronics.