



80A 68V N-CHANNEL POWER MOSFET

Description

This model is an advanced **trench** MOSFET with better characteristics, such as fast switching time, low gate charge and low on state resistance.


Such enhanced MOSFET are commonly used in switching power supplies and adapters for high-speed switching applications.

Features


- $R_{DS(ON)} \leq 8.3m\Omega$ @ $V_{GS}=10V$, $I_D=30A$
- Fast switching capability
- Low On-Resistance
- 100% Avalanche tested
- 100% ΔV_{DS} tested

Mechanical data

- Case: TO-252W
- Approx. Weight: 0.33g (0.012oz)
- RoHS compliant
- Case Material: "Green" molding compound, UL flammability classification 94V-0, "Halogen-free".



SYMBOL



Absolute Maximum Ratings (Ta=25°C, Unless Otherwise Specified)

Parameter	Symbols	Ratings	Units
Drain-Source Voltage	V_{DS}	68	V
Gate-Source Voltage	V_{GS}	± 20	V
Continuous Drain Current $T_c=25^\circ C$	I_D	80	A
Pulsed Drain Current (Note 2)	I_{DM}	320	A
Avalanche Energy Single Pulsed (Note 3)	E_{AS}	227	mJ
Power Dissipation ($T_c = 25^\circ C$)	P_D	50	W
Operating junction and storage temperature	T_J, T_{STG}	-55 ~ +150	°C

Notes:

1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.
Absolute maximum ratings are stress ratings only and functional device operation is not implied.
- 2.Repetitive Rating: Pulse width limited by maximum junction temperature.
- 3.L=0.5mH,VDD=50V, RG=25Ω,Starting TJ=25°C

Thermal Resistance

Parameter	Symbols	Ratings	Units
Thermal resistance, junction – case.	R_{thJC}	2.5	°C/W
Thermal resistance, junction – ambient(min. footprint)	R_{thJA}	63	°C/W



Electrical Characteristics (Ta=25°C, Unless Otherwise Specified)


Parameter	Symbols	Test Conditions	Min	Typ	Max	Units
Off Characteristics						
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} =0V, I _D =250uA	68			V
Drain-Source Leakage Current	I _{DSS}	V _{DS} =68V, V _{GS} =0V			1.0	uA
Gate- Source Leakage Current	Forward	I _{GSS}	V _{GS} =20V, V _{DS} =0V		100	nA
	Reverse		V _{GS} =-20V, V _{DS} =0V		-100	
On Characteristics						
Gate Threshold Voltage	V _{GS(TH)}	V _{DS} =V _{GS} , I _D =250uA	2.0		4.0	V
Static Drain-Source On-State Resistance	R _{D(S)} (ON)	V _{GS} =10V, I _D =30A		6.6	8.3	mΩ
Transconductance	g _{fs}	V _{DS} =20V, I _D =2.5A		5		S
Dynamic Characteristics						
Input Capacitance	C _{ISS}	V _{DS} =34V, V _{GS} =0V, f=1.0MHz		5504		pF
Output Capacitance	C _{OSS}			321		pF
Reverse Transfer Capacitance	C _{rss}			263		pF
Gate resistance	R _G	V _{DS} =0V, FREQ=1.00MHz		1		Ω
Switching Characteristics						
Total Gate Charge (Note 1)	Q _G	V _{DS} =34V, V _{GS} =10V, I _D =30A (NOTE1,2)		70		nC
Gate-Source Charge	Q _{GS}			24		nC
Gate-Drain Charge	Q _{GD}			17		nC
Turn-On Delay Time (Note 1)	t _{D(ON)}	V _{DS} =34V, I _D =30A R _G =3Ω, V _{GS} =10V (NOTE1,2)		19		ns
Turn-On Rise Time	t _R			27		ns
Turn-Off Delay Time	t _{D(OFF)}			37		ns
Turn-Off Fall Time	t _F			10		ns
Drain-Source Diode Characteristics And Maximum Ratings						
Maximum Body-Diode Continuous Current	I _S				80	A
Drain-Source Diode Forward Voltage (Note 1)	V _{SD}	I _{SD} =30A, V _{GS} =0V			1.2	V
Reverse Recovery Time (Note 1)	t _{rr}	I _F =30A di/dt=100A/us		31		ns
Reverse Recovery Charge	Q _{rr}			46		uC

Notes:


1. Pulse Test: Pulse width ≤ 300μs, Duty cycle ≤ 2%.
2. Essentially independent of operating temperature.




Test Circuits and waveforms




Switching Test Circuit




Switching Waveforms




Gate Charge Test Circuit



Gate Charge Waveform




Unclamped Inductive Switching Test Circuit




Unclamped Inductive Switching Waveforms



Test Circuits and waveforms



Peak Diode Recovery dv/dt Test Circuit





Typical Characteristics

Fig.1 Output characteristics




Fig.2 Power Dissipation




Fig.3 Drain Current Derating




Fig.4 Drain-Source On-Resistance vs. Drain Current




Fig.5 Gate Threshold Voltage vs. Junction Temperature




Fig.6 Body-diode Forward Characteristics




Fig.7 Drain-Source On-Resistance vs. Junction Temperature





Fig.8 Breakdown Voltage vs. Junction Temperature





Typical Characteristics

Fig.9 Capacitance Characteristics




Fig.10 Gate Charge Characteristics




Fig.11 Safe Operating Area






Fig.12 Max. Transient Thermal Impedance





TO-252W(D-PAK) Package Outline Dimensions




TO-252W(D-PAK) Mechanical data

UNIT	A	B	b	C	D	E	F	G	H	L	L1	L2	L3	S	M	N	J	T	K	
mm	max	6.7	5.53	0.86	2.5	6.3	0.61	1.87	2.3 typ.	0.55	3.1	1.2	1.0	1.90	0.1	1.8 typ.	1.3 typ.	3.2 ref.	5.23 ref.	1.8 ref.
	typ	6.6	5.33	0.76	2.3	6.1	0.51	1.57		0.50	2.95	1.0	0.8	1.45	0.05					
	min	6.3	5.13	0.66	2.1	5.9	0.41	1.27		0.45	2.7	0.8	0.6	1.00	/					
mil	max	264	218	34	98	248	24	74	91 typ.	22	121	47	39	75	3.9	71 typ.	51 typ.	126 ref.	206 ref.	71 ref.
	typ	260	210	30	91	240	20	62		20	116	39	31	57	2					
	min	248	202	26	83	232	16	50		18	106	31	24	39	/					

Marking

Type number	Marking code
D6R6N68HN	D6R6N68HN



SUGGESTED SOLDER PAD LAYOUT



Important Notice and Disclaimer

Jingdao Microelectronics reserves the right to make changes to this document and its products and specifications at any time without notice.

Customers should obtain and confirm the latest product information and specifications before final purchase or use.

Jingdao Microelectronics makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Jingdao Microelectronics assume any liability for application assistance or customer product design.

Jingdao Microelectronics does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of Jingdao Microelectronics.

Jingdao Microelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of Jingdao Microelectronics.