


Switching Diodes


FEATURES

- Fast Switching Speed
- For General Purpose Switching Applications
- High Conductance



PINNING

PIN	DESCRIPTION
a	Cathode
b	Anode



Maximum Ratings @Ta=25°C

Parameter	Symbol	Value	Unit
Reverse Voltage	V_R	70	V
Forward Current	I_F	200	mA
Non-Repetitive Peak Forward Surge Current @t=1ms	I_{FSM}	1.0	A
Power Dissipation	P_D	225	mW
Thermal Resistance Junction to Ambient	R_{thJA}	556	°C/W
Operation Junction and Storage Temperature Range	T_J, T_{STG}	-55 ~ +150	°C

Electrical Characteristics @Ta=25°C

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Reverse breakdown voltage	V_R	$I_R=100\mu A$	70			V
Forward voltage	V_{F1}	$I_F=1\text{ mA}$			0.7	V
	V_{F2}	$I_F=10\text{mA}$			0.855	V
	V_{F3}	$I_F=50\text{mA}$			1	V
	V_{F4}	$I_F=100\text{ mA}$			1.1	V
Reverse current	I_R	$V_R=70\text{V}$			0.1	μA
Capacitance between terminals	C_T	$V_R=0, f=1\text{MHz}$			2.0	pF
Reverse recovery time	t_{rr}	$I_F=I_R=10\text{mA}, I_{rr}=0.1 \times I_R, R_L=100\Omega$			4	ns



Fig.1 Power Derating Curve




Fig.2 Reverse Characteristics




Fig.3 Forward Characteristics






Fig.4 Capacitance Characteristics






SOT-23 Package Outline Dimensions



The recommended mounting pad size



Marking

Type number	Marking code
MMBD6100WD	61



Important Notice and Disclaimer

Jingdao Microelectronics reserves the right to make changes to this document and its products and specifications at any time without notice.

Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

Jingdao Microelectronics makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, not does Jingdao Microelectronics assume any liability for application assistance or customer product design.

Jingdao Microelectronics does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of Jingdao Microelectronics.

Jingdao Microelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of Jingdao Microelectronics.